

Flexi type unit

FLXS-B(9)



Home leave operation



Indoor unit silent operation



Vertical auto swing



VRV for residential application



Online controller via app

Flexible unit, ideal for rooms without false ceiling, can fit on either ceiling or wall

- › Can fit on either ceiling or lower wall; its low height enables the unit to fit beneath a window
- › Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- › Home leave operation maintains the indoor temperature at your specified comfort level during absence, thus saving energy
- › Online controller (optional): control your indoor unit from any location via smartphone, laptop, pc, tablet or touch screen

FLXS-B(9) + RXS-L(3)



Indoor unit		FLXS	25B	35B9	50B	60B
Casing	Colour	Almond white				
Dimensions	Unit	HeightxWidthxDepth	mm			
			490x1,050x200			
Sound power level	Cooling/Heating		51/51	53/59	60/-	60/59
Sound pressure level	Cooling	High/Nom./Low/Silent operation	37/34/31/28	38/35/32/29	47/43/39/36	48/45/41/39
	Heating	High/Nom./Low/Silent operation	37/34/31/29	46/36/33/30	46/41/35/33	47/42/37/34
Control systems	Infrared remote control	ARC433B67				


Efficiency data		FLXS + RXS	25B + 25L3	35B9 + 35L3	50B + 50L	60B	
Cooling capacity	Min./Nom./Max.	kW	1.2/2.5/3.0	-/3.5/-	0.9/4.9/5.3	-	
Heating capacity	Min./Nom./Max.	kW	1.2/3.4/4.5	1.4/4.0/5.0	0.9/6.1/7.5	-	
Power input	Cooling	Min./Nom./Max.	kW	0.300/0.668/0.860	0.300/1.215/1.260	0.450/1.720/1.950	-
	Heating	Min./Nom./Max.	kW	0.290/0.960/1.490	0.290/1.120/1.850	0.310/1.820/3.540	-
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A	B	A	Only available in multi model application
		Pdesign	kW	2.50	3.50	4.90	
		SEER		5.19	4.87	5.25	
		Annual energy consumption	kWh	169	252	326	
	Heating (Average climate)	Energy label		A			
		Pdesign	kW	2.50	2.90	4.20	
		SCOP			3.80		
		Annual energy consumption	kWh	921	1,068	1,546	
Nominal efficiency	EER		3.74	2.88	2.85		
	COP		3.54	3.57	3.35		
	Annual energy consumption	kWh	334	608	860		
	Energy label	Cooling/Heating		A/B	B/A	C/C	

Outdoor unit		RXS	25L3	35L3	50L	60B	
Dimensions	Unit	HeightxWidthxDepth	mm				
			550x765x285				
Sound power level	Cooling		59	61	62	Only available in multi model application	
	Heating		59	61	62		
Sound pressure level	Cooling	High/Low/Silent operation	dBA	46/-/43	48/-/44		48/44/-
	Heating	High/Low/Silent operation	dBA	47/-/44	48/-/45		48/45/-
Operation range	Cooling	Ambient	Min.-Max.	°CDB	-10~46		
	Heating	Ambient	Min.-Max.	°CWB	-15~18		
Refrigerant	Type/GWP	R-410A/2,087.5					
	Charge	kg/TCO ₂ eq	1.0/2.1	1.2/2.5	1.7/3.5		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240		1~/50/220-230-240		

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-030 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.